

Modification	Allowed in:						
	Stock	STS	STX	STS2	STU	Street Prepared	Street Mod
Suspension							
Shocks	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Springs	No	Yes	Yes	Yes	Yes	Yes	Yes
Front sway bar	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Rear sway bar	No	Yes	Yes	Yes	Yes	Yes	Yes
Strut tower bars	No	Yes	Yes	Yes	Yes	Yes	Yes
Tie bars (2-point only)	No	Yes ¹	Yes ¹	Yes ¹	Yes ¹	Yes ¹	Yes
Suspension bushings	No	Yes ²	Yes ²	Yes ²	Yes ²	Yes ²	Yes
Crash bolts	Yes ³	Yes	Yes	Yes	Yes	Yes	Yes
Camber plates	No	Yes	Yes	Yes	Yes	Yes	Yes
Traction bars, torque arms	No	Yes	Yes	Yes	Yes	Yes	Yes
Panhard bar	No	Yes	Yes	Yes	Yes	Yes	Yes
Camber kits	No	Yes	Yes	Yes	Yes	No	Yes
Subframe connectors	No	No	No	No	No	Yes	Yes
Subframe mount bushings	No	Yes	Yes ²	Yes ²	Yes ²	Yes ²	Yes
Engine							
Air filter	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Air intake	No	Yes	Yes	Yes	Yes	Yes	Yes
Throttle body	No	No	No	No	No	Yes	Yes
Intake manifold	No	No	No	No	No	Yes	Yes
Header(s)	No	Yes	Yes	Yes	Yes	Yes	Yes
Catalytic converter (replace/remove)	No	Yes, replace ⁴	Yes, replace ⁵	Yes, replace ⁴	Yes, replace ⁵	Yes	Yes
Test pipe	No	No	No	No	No	Yes	Yes
Exhaust (cat back)	Yes	Yes	Yes	Yes	Yes	Yes	Yes
ECU (modify/replace)	No	Yes, modify ⁶	Yes, modify ⁶	Yes, modify ⁶	Yes, modify ⁶	Yes, replace	Yes, replace
VTEC controller	No	Yes	Yes	Yes	Yes	Yes	Yes
Short throw shifter	No	Yes	Yes	Yes	Yes	Yes	Yes
Accessory pulleys	No	Yes	Yes	Yes	Yes	Yes	Yes
Cams	No	No	No	No	No	No	Yes
Cam gears	No	No	No	No	No	Yes ⁷	Yes
Pistons	No	No	No	No	No	Yes ⁸	Yes
Valvetrain	No	No	No	No	No	No	Yes
Connecting rods	No	No	No	No	No	No	Yes
Crankshaft	No	No	No	No	No	No	Yes
Headwork	No	No	No	No	No	Yes ⁹	Yes
Motor mounts	No	Yes	Yes	Yes	Yes	Yes	Yes
Spark plugs and wires	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Replace intercooler	No	No	No	No	No	Yes	Yes
Add intercooler	No	No	No	No	No	No	Yes
Replace/modify/add turbo	No	No	No	No	No	No	Yes
Blow-off valve	No	No	No	No	No	No	Yes
Bypass/diverter valve	No	No	No	No	No	Yes	Yes
Supercharger pulley	No	No	No	No	No	No	Yes

¹ 3-point bars are not permitted, except as a factory configuration. A factory 3-point bar may only be replaced by a 2-point bar.

² Replacement bushings may not have metal content greater than the factory bushings.

³ Where permitted by factory documentation.

⁴ Replacement cats must be of the OE quantity, type, and location.

⁵ Multiple cats may be replaced by any single cat, no further downstream than 6 inches from final OE cat.

⁶ Boost changes not permitted.

⁷ Where variable timing is not standard.

⁸ See rulebook for details.

⁹ Intake/exhaust ports may be modified one inch or less from the port/manifold interface. Heads may be milled to 0.010 inches maximum, or the amount specified in factory documentation.

Modification	Allowed in:						
	Stock	STS	STX	STS2	STU	Street Prepared	Street Mod
Accusump-type system	No	No	No	No	No	Yes	Yes
Fuel pump	No	No	No	No	No	Yes	Yes
Fuel tank	No	No	No	No	No	No	Yes
Fuel pressure regulator	No	Yes	Yes	Yes	Yes	Yes	Yes
Replace engine	No	No	No	No	No	No	Yes ¹⁰
Brakes							
Pads/shoes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Cross-drilled/slotted rotors	No	Yes	Yes	Yes	Yes	Yes	Yes
Replace drums with rotors & calipers	No	No	Yes	No	Yes	No	Yes
Replace stock rotors and/or calipers with larger units	No	No	Yes	No	Yes	No	Yes
Two-piece rotors	No	No	Yes	No	Yes	No	Yes
Calipers	No	No	Yes	No	Yes	No	Yes
DOT-approved brake lines	Yes ¹¹	Yes	Yes	Yes	Yes	Yes	Yes
Speedbleeders	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Wheels & Tires							
Street tires, treadwear 140 or higher	Yes	Yes ¹²	Yes ¹³	Yes ¹²	Yes ¹⁴	Yes	Yes
DOT-approved R-compound tires	Yes	No	No	No	No	Yes	Yes
Racing slicks	No	No	No	No	No	No	No
Wheels, stock diameter, width, & offset ±0.25 inch	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Wheels, any diameter	No	Yes ¹²	Yes ¹³	Yes ¹²	Yes ¹⁴	Yes	Yes
Body work							
Accessories, gauges, indicators, lights, etc	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Alternate steering wheel (original has airbag)	No	No	No	No	No	Yes	Yes
Alternate steering wheel (original doesn't have airbag)	Yes ¹⁵	Yes	Yes	Yes	Yes	Yes	Yes
Roll bars/cages	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Driver/passenger harnesses	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Harness bar	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Trailer hitch	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Pedal kits	No	Yes	Yes	Yes	Yes	Yes	Yes
Cut/flared fenders	No	No	No	No	No	Yes	Yes
Rolled fenders	No	Yes	Yes	Yes	Yes	Yes	Yes
Replacement fenders	No	No	No	No	No	No	Yes
Spoiler	No	Yes	Yes	Yes	Yes	Yes	Yes
Wing	No	Yes	Yes	Yes	Yes	No	Yes
Splitter	No	Yes	Yes	Yes	Yes	Yes	Yes
Body kit	No	Yes	Yes	Yes	Yes	Yes	Yes
Replace hood	No	No	No	No	No	No	Yes
Replace hatch/trunk	No	No	No	No	No	No	No
Replace front seats	No	Yes ¹⁶	Yes ¹⁶	Yes ¹⁶	Yes ¹⁶	Yes	Yes
Remove passenger seat	No	No	No	No	No	No	No
Remove rear seat	No	No	No	No	No	No	Yes
Fuel cell	No	No	No	No	No	No ¹⁷	Yes

¹⁰ Only an engine from the same manufacturer is permitted.

¹¹ Only on vehicles produced before 1992.

¹² Wheel/tire maximum widths: 7.5 inches, 225 mm.

¹³ Wheel/tire maximum widths: 8.0 inches, 245 mm.

¹⁴ Wheel/tire maximum widths: unlimited, 245 mm (AWD), 275 mm (2WD).

¹⁵ Outer diameter must be within 1 inch of OE.

¹⁶ Seats must weigh at least 25 pounds including mounting hardware, and the top of the seat/headrest may not be below the center of the driver's head.

Modification	Allowed in:						
	Stock	STS	STX	STS2	STU	Street Prepared	Street Mod
Transmission							
Add/replace LSD	No	No	Yes	No	Yes	Yes	Yes
Replace transmission	No	No	No	No	No	No	Yes
Transmission mount bushing	No	Yes ²	Yes ²	Yes ²	Yes ²	Yes ²	Yes
Gears	No	No	No	No	No	No	Yes
Differential	No	No	No	No	No	Yes	Yes
Differential mount bushing	No	Yes ²	Yes ²	Yes ²	Yes ²	Yes ²	Yes
Driveshaft	No	No	No	No	No	No	Yes
Clutch	No	No	No	No	No	Yes	Yes
Flywheel	No	No	No	No	No	Yes	Yes
Other							
Battery, original voltage, any size/shape	No	Yes	Yes	Yes	Yes	Yes	Yes
Battery, not original voltage, any size/shape	No	No	No	No	No	No	No
Battery relocation	No	Yes	Yes	Yes	Yes	Yes	Yes
Remove air conditioning	No	No	No	No	No	Yes	Yes
Remove power steering	No	No	No	No	No	No	Yes
Remove ABS	No	No	No	No	No	Disable, not remove	Yes
Steering rack bushings	No	Yes ²	Yes ²	Yes ²	Yes ²	Yes ²	Yes

¹⁷ Fuel cells are permitted provided the vehicle is GCR-legal.